

TIME-BASED AIRCRAFT/ATC OPERATIONS STUDY

David H. Williams NASA Langley Research Center




TIME-BASED AIRCRAFT/ATC OPERATIONS STUDY (JOINT LARC /ARC SIMULATION)



STUDY OBJECTIVES

- DEVELOP AND EVALUATE PROCEDURES FOR INCORPORATING 4D-EQUIPPED AIRCRAFT INTO A 4D ATC SYSTEM
- DETERMINE IMPACT ON THE SYSTEM OF DISSIMILAR AIRBORNE AND GROUND 4D SPEED STRATEGIES
- EVALUATE EFFECTIVENESS OF AIRBORNE TIME GUIDANCE

ORIGINAL PAGE BLACK AND WHITE PHOTOGRAPH



NASA TSRV 4D FMS CAPABILITIES

TRAJECTORY GENERATION

HORIZONTAL ROUTE DEFINED THROUGH FLEXIBLE CDU OPERATIONS. (COMPARABLE TO B-737-400)


VERTICAL TRAJECTORY GENERATION WITH ARRIVAL TIME CONSTRAINT.

- MINIMUM FUEL
- ATC DESCENT ADVISOR


AUTOMATIC RECALCULATION CAPABILITY.

4D GUIDANCE

VERTICAL SITUATION DISPLAY WITH TIME CAPABILITIES SHOWN AT ARRIVAL FIX. TIME-BASED ENERGY ERROR DISPLAY.




TSRV VERTICAL SITUATION DISPLAY



ACTIVE GUIDANCE MODE

TSRV VERTICAL SITUATION DISPLAY



265

AIRBORNE 4D PROCEDURES


TIME CLEARANCE

- ACKNOWLEDGE ATC
- ENTER ARRIVAL TIME
- EXECUTE NEW VERTICAL PROFILE
- ADVISE ATC OF SPEED CHANGE

• TIME DELAY VECTOR

- ACKNOWLEDGE ATC
- FLY ATC-SPECIFIED VECTOR AT MINIMUM SPEED
- ADVISE ATC OF SPEED CHANGE
- ENTER ARRIVAL TIME
- SELECT DIRECT INTERCEPT OF ATC-SPECIFIED WAYPOINT </ AUTOMATIC PROFILE RECALCULATION >>
- EXECUTE NEW PROFILE WHEN TIME DELAY COMPLETE
- ADVISE ATC WHEN TURNING BACK

TEST SCENARIO




TEST CONDITIONS

	CONDITION NUMBER				
	1	2	3	4	5
TRAFFIC LEVEL					
MODERATE	Х	X	X		
HEAVY			·	X	X
SPEED STRATEGY					
MINIMUM FUEL		Х	Х		х
DESCENT ADVISOR	Х			Х	
HORIZONTAL ROUTE					
NORMAL	×	X		X	х
OFFSET			Х		
total number of runs (3 pilots)	6	9	4	7	2

RESULTS

- TIME CLEARANCES, PROCEDURES AND DISPLAYS WELL RECEIVED BY PILOTS
- DISSIMILAR AIR AND GROUND SPEED STRATEGIES PRODUCED POTENTIAL TRAFFIC CONFLICTS DURING MODERATE TRAFFIC
 - ATC VECTORS AND ROUTE-OFFSET PROVED LESS EFFICIENT
 - CRUISE SPEED RESTRICTION COULD ALLEVIATE THE PROBLEM
- TIME DELAY VECTOR USEFUL DURING HEAVY TRAFFIC
 - POTENTIAL FOR RELIEVING CONTROLLER WORKLOAD
 - ALLOWS AIRCRAFT TO MINIMIZE DELAY RANGE
 - DISSIMILAR SPEEDS NOT A PROBLEM
- TIME GUIDANCE PROVED VERY EFFECTIVE
 - ARRIVAL TIME ERROR OF 2.9 SECONDS (STANDARD DEVIATION)

SEPARATION CONFLICT INDUCED BY DISSIMILAR SPEED SCHEDULES



Enroute separation for 32 minute flight time with 80 seconds in-trail separation at initial and final conditions

FUEL USAGE OF TSRV SIMULATOR

Aircraft Speed Strategy Route		ATC Interruption	Number of runs	Average Fuel Used	
Descent Advisor	normal	no	6	1779 (reference)	
Minimum fuel	normal	no	6	1740 (-2.2%)	
Minimum fuel	normal	yes	3	1891 (+6.3%)	
Minimum fuel	offset	no	3	1800 (+1.2%)	
Minimum fuel	offset	yes	1	1916 (+7.7%)	

FUTURE PLANS

- TEST PROCEDURAL SOLUTIONS TO COMPATIBILITY PROBLEMS OF DISSIMILAR SPEED STRATEGIES
- EXPLORE DATA LINK APPLICATIONS
 - UPLINK OF CLEARANCES AND SPEED CONSTRAINTS
 - DOWNLINK OF PLANNED SPEED SCHEDULE AND TOP OF DESCENT
- INTEGRATE TIME GUIDANCE INTO PRIMARY DISPLAYS
- DETERMINE WIND AND TEMPERATURE MODELING REQUIREMENTS
- TEST SCENARIOS WITH MULTIPLE 4D AIRCRAFT

SUMMARY

- AIRBORNE 4D CAN BE EFFECTIVELY INTEGRATED INTO AN ADVANCED 4D ATC SYSTEM
- DIFFERENCES IN 4D SPEED STRATEGIES CAN BE MANAGED WITH PROCEDURAL SOLUTIONS
- TIME GUIDANCE CONCEPTS VERY EFFECTIVE
 - MUST NOW BE INTEGRATED INTO AIRLINE COCKPIT

English the second of the seco		•